


SKP-D

DIN 46235 TYPE TUBULAR CABLE LUGS



All rights reserved.

Order Code	Cable Section (mm ²)	Bolt	Dimensions								Box Pcs.	Box Weight	Parcel Pcs.	Box Weight
			d1	d4	a	d2	b	c1	c2	L				
SKP-D/006-M05	6	M5	3.8	5.5	10.0	5.3	8.5	6.5	7.5	24.0	600	~1.9 kg.	3.600	~11.4 kg.
SKP-D/006-M06/SD		M6	3.8	5.5	10.0	6.4	8.5	7.5	8.0	24.0	600	~1.8 kg.	3.600	~10.8 kg.
SKP-D/006-M08		M8	3.8	5.5	10.0	8.4	13.0	10.0	10.0	24.0	600	~1.9 kg.	3.600	~11.4 kg.
SKP-D/010-M05	10	M5	4.5	6.0	10.0	5.3	9.0	7.0	8.5	27.0	500	~1.8 kg.	3.000	~10.8 kg.
SKP-D/010-M06/SD		M6	4.5	6.0	10.0	6.4	9.0	7.5	8.5	27.0	500	~1.7 kg.	3.000	~10.2 kg.
SKP-D/010-M08		M8	4.5	6.0	10.0	8.4	13.0	10.0	10.0	27.0	500	~1.8 kg.	3.000	~10.8 kg.
SKP-D/016-M06	16	M6	5.5	8.5	20.0	6.4	13.0	7.5	8.0	36.0	200	~2.4 kg.	1.200	~14.4 kg.
SKP-D/016-M08/SD		M8	5.5	8.5	20.0	8.4	13.0	10.0	10.0	36.0	200	~2.4 kg.	1.200	~14.4 kg.
SKP-D/016-M10		M10	5.5	8.5	20.0	10.5	17.0	12.0	12.0	36.0	200	~2.4 kg.	1.200	~14.4 kg.
SKP-D/016-M12		M12	5.5	8.5	20.0	13.0	18.0	13.0	13.0	36.0	200	~2.4 kg.	1.200	~14.4 kg.
SKP-D/025-M06	25	M6	7.0	10.0	20.0	6.4	14.0	7.5	8.0	38.0	175	~2.6 kg.	1.050	~15.6 kg.
SKP-D/025-M08/SD		M8	7.0	10.0	20.0	8.4	16.0	10.0	10.0	38.0	175	~2.7 kg.	1.050	~16.2 kg.
SKP-D/025-M10		M10	7.0	10.0	20.0	10.5	17.0	12.0	12.0	38.0	175	~2.7 kg.	1.050	~16.2 kg.
SKP-D/025-M12		M12	7.0	10.0	20.0	13.0	19.0	13.0	13.0	38.0	150	~2.3 kg.	900	~13.8 kg.
SKP-D/035-M06	35	M6	8.2	12.5	20.0	6.4	17.0	7.5	8.0	42.0	100	~2.8 kg.	600	~16.8 kg.
SKP-D/035-M08		M8	8.2	12.5	20.0	8.4	17.0	10.0	10.0	42.0	100	~2.8 kg.	600	~16.8 kg.
SKP-D/035-M10/SD		M10	8.2	12.5	20.0	10.5	19.0	12.0	12.0	42.0	100	~3.0 kg.	600	~18.0 kg.
SKP-D/035-M12		M12	8.2	12.5	20.0	13.0	21.0	13.0	13.0	42.0	100	~2.8 kg.	600	~16.8 kg.
SKP-D/035-M14		M14	8.2	12.5	20.0	15.0	21.0	14.5	14.5	42.0	100	~2.6 kg.	600	~15.6 kg.
SKP-D/050-M08	50	M8	10.0	14.5	28.0	8.4	20.0	10.0	10.0	52.0	60	~2.7 kg.	360	~16.2 kg.
SKP-D/050-M10/SD		M10	10.0	14.5	28.0	10.5	22.0	12.0	12.0	52.0	60	~2.7 kg.	360	~16.2 kg.
SKP-D/050-M12		M12	10.0	14.5	28.0	13.0	24.0	13.0	13.0	52.0	60	~2.7 kg.	360	~16.2 kg.
SKP-D/050-M14		M14	10.0	14.5	28.0	15.0	24.0	14.5	14.5	52.0	60	~2.7 kg.	360	~16.2 kg.
SKP-D/050-M16	70	M16	10.0	14.5	28.0	17.0	28.0	16.0	16.0	52.0	60	~2.7 kg.	360	~16.2 kg.
SKP-D/070-M08		M8	11.5	16.5	28.0	8.4	24.0	10.0	10.0	55.0	50	~3.0 kg.	300	~18.0 kg.
SKP-D/070-M10/SD		M10	11.5	16.5	28.0	10.5	24.0	12.0	12.0	55.0	50	~3.1 kg.	300	~18.6 kg.
SKP-D/070-M12		M12	11.5	16.5	28.0	13.0	24.0	13.0	13.0	55.0	50	~3.0 kg.	300	~18.0 kg.
SKP-D/070-M14		M14	11.5	16.5	28.0	15.0	24.0	14.5	14.5	55.0	50	~3.0 kg.	300	~18.0 kg.
SKP-D/070-M16	95	M16	11.5	16.5	28.0	17.0	30.0	16.0	16.0	55.0	50	~3.0 kg.	300	~18.0 kg.
SKP-D/095-M08		M8	13.5	19.0	35.0	8.4	28.0	12.0	12.0	65.0	35	~3.2 kg.	210	~19.2 kg.
SKP-D/095-M10		M10	13.5	19.0	35.0	10.5	28.0	12.0	12.0	65.0	35	~3.2 kg.	210	~19.2 kg.
SKP-D/095-M12/SD		M12	13.5	19.0	35.0	13.0	28.0	13.0	13.0	65.0	35	~3.1 kg.	210	~18.6 kg.
SKP-D/095-M14		M14	13.5	19.0	35.0	15.0	28.0	14.5	14.5	65.0	35	~3.2 kg.	210	~19.2 kg.
SKP-D/095-M16	120	M16	13.5	19.0	35.0	17.0	32.0	16.0	16.0	65.0	35	~3.2 kg.	210	~19.2 kg.
SKP-D/120-M10		M10	15.5	21.0	35.0	10.5	32.0	15.0	16.0	70.0	30	~3.4 kg.	180	~20.4 kg.
SKP-D/120-M12/SD		M12	15.5	21.0	35.0	13.0	32.0	16.0	17.0	70.0	30	~3.4 kg.	180	~20.4 kg.
SKP-D/120-M14		M14	15.5	21.0	35.0	15.0	32.0	18.0	19.0	70.0	30	~3.4 kg.	180	~20.4 kg.
SKP-D/120-M16		M16	15.5	21.0	35.0	17.0	32.0	19.0	20.0	70.0	30	~3.4 kg.	180	~20.4 kg.
SKP-D/120-M20	120	M20	15.5	21.0	35.0	21.0	38.0	21.0	22.0	70.0	30	~3.4 kg.	180	~20.4 kg.

Order Code	Cable Section (mm ²)	Bolt	Dimensions								Box Pcs.	Box Weight	Parcel Pcs.	Box Weight
			d1	d4	a	d2	b	c1	c2	L				
SKP-D/150-M10	150	M10	17,0	23,5	35,0	10,5	34,0	15,0	16,0	78,0	15	~2,5 kg.	90	~15,0 kg.
SKP-D/150-M12/SD		M12	17,0	23,5	35,0	13,0	34,0	16,0	17,0	78,0	15	~2,5 kg.	90	~15,0 kg.
SKP-D/150-M14		M14	17,0	23,5	35,0	15,0	34,0	19,0	20,0	78,0	15	~2,5 kg.	90	~15,0 kg.
SKP-D/150-M16		M16	17,0	23,5	35,0	17,0	34,0	19,0	20,0	78,0	15	~2,5 kg.	90	~15,0 kg.
SKP-D/150-M20		M20	17,0	23,5	35,0	21,0	40,0	21,0	22,0	78,0	15	~2,4 kg.	90	~14,4 kg.
SKP-D/185-M10	185	M10	19,0	25,5	40,0	10,5	37,0	15,0	16,0	82,0	12	~2,3 kg.	72	~13,8 kg.
SKP-D/185-M12/SD		M12	19,0	25,5	40,0	13,0	37,0	16,0	17,0	82,0	12	~2,3 kg.	72	~13,8 kg.
SKP-D/185-M14		M14	19,0	25,5	40,0	15,0	37,0	19,0	20,0	82,0	12	~2,3 kg.	72	~13,8 kg.
SKP-D/185-M16		M16	19,0	25,5	40,0	17,0	37,0	19,0	20,0	82,0	12	~2,3 kg.	72	~13,8 kg.
SKP-D/185-M20		M20	19,0	25,5	40,0	21,0	40,0	21,0	22,0	82,0	12	~2,2 kg.	72	~13,2 kg.
SKP-D/240-M12/SD	240	M12	21,5	29,0	40,0	13,0	42,0	16,0	17,0	92,0	8	~2,2 kg.	48	~13,2 kg.
SKP-D/240-M14		M14	21,5	29,0	40,0	15,0	42,0	19,0	20,0	92,0	8	~2,3 kg.	48	~13,8 kg.
SKP-D/240-M16		M16	21,5	29,0	40,0	17,0	42,0	19,0	20,0	92,0	8	~2,2 kg.	48	~13,2 kg.
SKP-D/240-M20		M20	21,5	29,0	40,0	21,0	45,0	21,0	22,0	92,0	8	~2,2 kg.	48	~13,2 kg.
SKP-D/300-M14	300	M14	24,5	32,0	50,0	15,0	48,0	19,0	22,0	100,0	8	~2,7 kg.	48	~16,2 kg.
SKP-D/300-M16/SD		M16	24,5	32,0	50,0	17,0	48,0	19,0	22,0	100,0	8	~2,7 kg.	48	~16,2 kg.
SKP-D/300-M20		M20	24,5	32,0	50,0	21,0	48,0	22,0	22,0	100,0	8	~2,7 kg.	48	~16,2 kg.
SKP-D/400-M14	400	M14	27,5	38,5	70,0	15,0	55,0	25,0	25,0	115,0	5	~3,4 kg.	30	~20,4 kg.
SKP-D/400-M16/SD		M16	27,5	38,5	70,0	17,0	55,0	25,0	25,0	115,0	5	~3,3 kg.	30	~19,8 kg.
SKP-D/400-M20		M20	27,5	38,5	70,0	21,0	55,0	25,0	25,0	115,0	5	~3,2 kg.	30	~19,2 kg.
SKP-D/500-M16	500	M16	31,0	42,0	70,0	17,0	60,0	25,0	25,0	125,0	4	~3,4 kg.	24	~20,4 kg.
SKP-D/500-M20/SD		M20	31,0	42,0	70,0	21,0	60,0	25,0	25,0	125,0	4	~3,3 kg.	24	~19,8 kg.
SKP-D/625-M16	625	M16	34,5	44,0	80,0	17,0	60,0	25,0	25,0	135,0	3	~2,6 kg.	18	~15,6 kg.
SKP-D/625-M20/SD		M20	34,5	44,0	80,0	21,0	60,0	25,0	25,0	135,0	3	~2,5 kg.	18	~15,0 kg.
SKP-D/800-M16	800	M16	40,0	52,0	100,0	17,0	75,0	30,0	30,0	165,0	4	~6,2 kg.	8	~12,4 kg.
SKP-D/800-M20/SD		M20	40,0	52,0	100,0	21,0	75,0	30,0	30,0	165,0	4	~6,0 kg.	8	~12,0 kg.
SKP-D/1000-M16	1000	M16	44,0	58,0	100,0	17,0	85,0	30,0	30,0	165,0	4	~8,0 kg.	24	~48,0 kg.
SKP-D/1000-M20/SD		M20	44,0	58,0	100,0	21,0	85,0	30,0	30,0	165,0	4	~7,4 kg.	24	~44,4 kg.

SKP-D SPECIFICATIONS

MATERIAL	ELECTROLYTIC COPPER CONFORMED TO EN 13600
COATING	TIN PLATED
JOINT	CLAMP COUPLING
CONFORMED TO DIN 46235	

THE CABLE LUGS WHICH ARE INDICATED IN BOLD FONT, ARE STANDARD PRODUCTS OF **Simpa**

