


SP-IKY

INSULATED CABLE END-SLEEVES



All rights reserved.

Order Code	Cable Section (mm ²)	Dimensions						Color	Box Pcs.	Box Weight
		c	a	L	W	d4	d1			
SP-IKY/0,50-8	0,5	6,0	8,0	14,0	2,6	1,3	1,0	Orange	1.000	~0,2 kg.
SP-IKY/0,75-8	0,75	6,0	8,0	14,0	2,8	1,5	1,2	White	1.000	~0,3 kg.
SP-IKY/1,0-8	1	6,0	8,0	14,0	3,0	1,7	1,4	Yellow	1.000	~0,1 kg.
SP-IKY/1,5-8	1,5	6,0	8,0	14,0	3,5	2,0	1,7	Red	700	~0,1 kg.
SP-IKY/1,5-10		6,0	10,0	16,0	3,5	2,0	1,7	Red	600	~0,2 kg.
SP-IKY/1,5-18		6,0	18,0	24,0	3,5	2,0	1,7	Red	400	~0,2 kg.
SP-IKY/2,5-8	2,5	7,0	8,0	15,0	4,0	2,6	2,3	Blue	500	~0,3 kg.
SP-IKY/2,5-12		7,0	10,0	17,0	4,0	2,6	2,3	Blue	400	~0,2 kg.
SP-IKY/2,5-18		7,0	18,0	25,0	4,0	2,6	2,3	Blue	300	~0,2 kg.
SP-IKY/4-10	4	7,0	9,0	16,0	4,4	3,2	2,8	Grey	250	~0,1 kg.
SP-IKY/4-12		8,0	12,0	20,0	4,4	3,2	2,8	Grey	250	~0,2 kg.
SP-IKY/6-12	6	8,0	12,0	20,0	6,3	3,9	3,5	Black	200	~0,2 kg.
SP-IKY/10-12	10	9,0	12,0	21,0	7,6	4,9	4,5	Ivory	100	~0,1 kg.
SP-IKY/16-12	16	10,0	12,0	22,0	8,8	6,2	5,8	Green	50	~0,1 kg.
SP-IKY/16-18		10,0	18,0	28,0	8,8	6,2	5,8	Green	50	~0,1 kg.
SP-IKY/25-16	25	13,0	16,0	29,0	11,2	7,9	7,5	Brown	40	~0,1 kg.
SP-IKY/35-16	35	14,0	16,0	30,0	12,7	8,7	8,3	Beige	20	~0,1 kg.
SP-IKY/50-20	50	16,0	20,0	36,0	15,3	10,9	10,3	Ol. Green	20	~0,1 kg.
SP-IKY/70-20	70	16,0	20,0	36,0	16,0	14,3	13,5	Yellow	15	~0,1 kg.
SP-IKY/95-25	95	18,5	24,5	43,0	18,0	15,6	14,6	Red	8	~0,1 kg.
SP-IKY/120-27	120	20,0	27,0	47,0	20,0	17,7	16,7	Blue	5	~0,1 kg.

FOR THE INSULATED CABLE END-SLEEVES, THE FIRST PART OF THE PRODUCT CODE INDICATES THE DIAMETER AND THE SECOND PART INDICATES THE LENGTH OF THE PRODUCT.

CONFORMED TO GERMAN COLOR STANDARD.

SK-IKY SPECIFICATIONS

MATERIAL	COPPER
COATING	TIN PLATED
INSULATION	POLYPROPYLENE
CONFORMED TO	DIN 46228

